



Product Catalog

Submersible Borewell Pumps & Openwell Monoset Pumpsets

ISO 9001 Registered Company
B-8, Balaji Estate, B/h. G.D. High School, Sajpur Bogha, Ahmedabad, Gujarat, India
+91 97234 68606 / +91 82003 37004

Submersible Borewell Pump



V-4 Submersible Borewell Pump

V-4 oil / water lubricated pumpset, light weight and easy to install.

Power Range	Single Phase: 0.37 kW – 3.7 kW (0.5 HP – 5.0 HP) Three Phase: 0.75 kW – 7.5 kW (1.0 HP – 10.0 HP)
Speed	2850 RPM, 50Hz, AC Supply
Version	Single Phase 160–240V, Three Phase 200–415V
Maximum Total Head	360 Metre
Discharge Range	8 – 524 LPM
Stage	Up to 60 stage
Normal Outlet Size	25, 32, 38, 50 & 65 mm
Degree of Protection	IP 68
Suitable Bore Diameter	100 mm



V-5 Submersible Borewell Pump

V-5 submersible borewell pumpset with stainless steel stator body.

V-6 Submersible Borewell Pump

V-6 water lubricated pumpset for high-head, high-discharge applications.



Power Range	Single Phase: 2.2 kW – 3.7 kW (3.0 HP – 5.0 HP) Three Phase: 2.2 kW – 26.0 kW (3.0 HP – 36.0 HP)
Speed	2900 RPM, 50Hz, AC Supply
Version	Single Phase 160–240V, Three Phase 200–415V
Maximum Total Head	360 Metre
Discharge Range	20 – 1550 LPM
Maximum Stage	Up to 30 stage
Normal Outlet Size	50, 65, 80 & 100 mm
Degree of Protection	IP 68
Suitable Bore Diameter	150 mm

Openwell Monoset Pump

Horizontal Openwell Submersible Monoset

Star-rated energy efficient openwell monoset for wide voltage fluctuations.



Power Range	Single Phase: 0.37 kW – 3.7 kW (0.5 HP – 5.0 HP) Three Phase: 0.75 kW – 11.0 kW (1.0 HP – 15.0 HP)
Speed	2900 RPM, 50Hz, AC Supply
Version	Single Phase 160–240V, Three Phase 200–400V
Maximum Total Head	Single Phase – 37 Metre, Three Phase – 50 Metre
Discharge Range	Single Phase: 35 – 909 LPM Three Phase: 25 – 2105 LPM
Stage	1 Stage
Normal Outlet Size	25, 40, 50, 65, 75, 100 mm
Degree of Protection	IP 68
Direction of Rotation	Single Phase – counter clockwise from driving end Three Phase – electrically reversible